

MSPOE16X 16-port 2 Uplink port PoE Switch



Key Features:

- ✓ Multiple working modes to address your business needs: Normal, Secure and Surveillance
- ✓ Support port traffic control
- ✓ Support for secure mode, all downlink ports can communicate only with uplink ports
- ✓ Up to 250m transmission distance on surveillance mode
- ✓ Support buffer optimization
- ✓ All metal housing, safe and reliable

Specifications

Ports	16×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az
Switching capacity	7.2Gbps
Forwarding performance	5.36Mpps
Packet Buffer	4M bit
MAC	16K
Dimensions (W×D×H)	440mm x 207mm x 44mm (17.3"×8.1"×1.7")
Weight	<4.2kg
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af
Max. PoE Power	Max capacity: 250W Max capacity for single port: 30W
Cooling Fans	2
Mean Time Between Failure (MTBF)	>50000 hours
Operating temperature	0°C-40°C (32°F-104°F)
Operating humidity	10%~90% (noncondensing)
Storage temperature	5%~90% (noncondensing)
Indicator	PWR:

	Steady on: AC input is normal Off: No AC input
	PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal
	LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data
	Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps
Working Mode	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. EXTEND(Surveillance mode): Transmission distance up to 250 meters.

© COPYRIGHT 2019. This documentation served as a reference only. It is subject to change without further notice. All the diagrams and information in this documentation may not be duplicated or modified in any form without the written approval from the management.